

WATERPROOFING CATALOGUE



An ISO 9001:2015
Certified Company





Introduction

Kavalani & Sons is **An ISO 9001:2015 certified**, professionally managed organization, committed to offering complete customer satisfaction. We are Bahrain's most innovative supplier of **Industrial, Construction, Safety, HVAC, Electrical, Plumbing, Waterproofing, Interior and Marine Equipment** and have been in the market for more than 60 Years.

We offer more than 60,000 products from the world's market leading brands under one roof. We strongly believe in innovation and are constantly on the look out to bring innovative products and solutions to the market.

Our quest to introduce new state-of-the-art technologies and products has led to our diversification across different divisions and product lines. Our customers come to us expecting more than just a product, they look out for solutions.

We are pleased to introduce our **WATERPROOFING PRODUCT CATALOGUE** which brings together all reputed brands with International Standard into one Single Source.

ONE SOURCE, MANY SOLUTIONS



CONTENTS

APP & SBS MEMBRANE



02

APP & SBS MEMBRANE



03

APP | PVC | EPDM MEMBRANE




04

ACRYLIC | ELASTOMERIC | PU COATING



05

POLYURETHANE FOAM & POLYUREA



06

EPOXY | PU | LIGHTWEIGHT CHEMICALS



07

HEAT INSULATION SYSTEM



08

EXPANSION JOINT SYSTEM



09

PROTECTION & SEPARATION LAYERS



10

MACHINERIES



11

MACHINERIES



12

INJECTION SYSTEM



13

TAPES & SEALANTS



14

TOOLS & ACCESSORIES



15

TOOLS & ACCESSORIES



16

OTHER PRODUCTS



17



Stoper

Made in
Türkiye



ISO
9001:2008
REGISTERED



Stoper AS is an investment of Ravago Group Co., the multi-national group of companies at 40 countries through its 200 member companies and 4000 employees worldwide.

Stoper plant, established on a very strategic location offering outstanding transportation benefits, has allowed Ravago Group to combine its long standing industrial and commercial experience and know how with the strength of being direct supplier of bituminous membranes.

Stoper has an accredited laboratory at its own premises capable of making all tests for bituminous membranes.

Thickness	: 1mm to 6mm
Size	: 1mtr x 10mtr
Type	: APP,SBS,Self-Adhesive
Finish	: PE & Mineral(Slate)

Available Colors



SPECIAL PRODUCTS

stickySTOPER membran

Self Adhesive Membranes...
Easy Applications !

gardenSTOPER membran

Nice terrace gardens with anti
root functionality!

viaSTOPER membran

Safer Road & Bridges !

APP & SBS MEMBRANE

BITUMEX

Made in
Türkiye

Along with being one of the leading membrane suppliers in Turkey with its many prestigious projects, Stoper AS also enjoys having its products distributed in 40 countries around the world through its reliable business partners.



Thickness : 1mm to 6mm
Size : 1mtr x 10mtr
Type : APP
Finish : PE & Mineral(Slate)



ITALIAN MEMBRANE



The company produces bitumen modified waterproofing membranes, APP, SBS and POE, self-adhesive membranes, heat insulation laminated to waterproofing membranes, bitumen shingles and water-based protective liquids. This wide range of products has over the years successfully been competing in quality and innovation with other producers in European countries.

Products



- Traditional App/sbs Membranes
- Light Weight Membranes
- Bituminous Shingles
- Separation Layers

- Single Layer Membranes
- Metal Finish Membranes
- Thermal Insulations
- Protective Paints




Application


- Flat Roofs
- Pitched Roofs
- Vaulted Roofs
- Roof Gardens



- Roads
- Bridges
- Viaducts
- Foundations



- Tunnels
- Water reservoirs
- Radon barriers
- Terraces



EGYPTIAN MEMBRANE



APAO modified membranes are innovative products that combine the advantages of APP membranes with those of SBS membranes, This means that the same membrane can have a softening point as high as 155° c coupled with a cold flexibility temperature as low as -30° c.

Thickness	: 3mm,3.5mm & 4mm
Size	: 1mtr x 10mtr
Type	: APP, SBS, APPO
Finsh	: PE & Mineral(Slate)



IZOMAR



BITUMODE



HYPERFLEX

APP & SBS MEMBRANE

izomaks

SAUDI MEMBRANE



Izomax CLASSIC: App Modified, Plastomeric Bituminous Waterproofing Membrane

Izomax VIA: App Modified, Plastomeric Bituminous Waterproofing Membrane


Izomax GOLD: SBS modified, elastomeric bitumen waterproofing membranes

Izomax GREEN LAND: Root Resistant Polymer Modified Bitumen Waterproofing Membranes

Polione: App Modified, Plastomeric Bituminous Waterproofing Membrane



POLARIS international
polymeric waterproofing industries



PVC MEMBRANE

Features


1. No Torch required - Safe Application Tools.
2. PVC Membrane is an easy apply system using hot air welding for joints.
3. Adhesives or primers are not required for installation.
4. Self extinguishing material in case of fire.
5. It is resistant to high temperature fluctuations.
6. Minimum slope is sufficient.
7. PVC membrane remains flexible throughout its life span.

MEMBRANE

COPERNIT
WATERPROOFING PRODUCTS

Bituminous SHINGLE

Flexible bituminous roofing shingle with, high bitumen content, glass fiber carrier and ceramized coloured granules finishing.




APP | PVC | EPDM



OHIO Waterproofing Systems

Advantage of EPDM Membrane

- Long-lasting performance
- Flexibility
- Outstanding weathering characteristics
- Unmatched resistance to ozone, UV radiation and cold cracking
- Dimensionally stable
- Limited environmental impact
- Low life-cycle cost





Origin: Made in UAE



Star Adhesives & Resin Inc. factory was established in 2000 and is one of the leading manufactures of a versatile range of technical advanced water based and solvent based products. Our products are widely acclaimed in the various kinds of industries apart from the construction industry through out the GCC and other neighbouring countries. We seek to be recognized as a world class manufacturer, providing its product and service through a dynamic working environment that attract and retain the finest talent and expertise.



STAROOF 602

HIGH PERFORMANCE COLD APPLIED SINGLE COMPONENT WATERPROOFING MEMBRANE.



STAROOF 800

SPECIAL SYNTHETIC RESIN BASED ELASTOMERIC WATERPROOF COATING.

Application

Suitable for waterproofing and protection for wet areas, kitchens, substructures, shaded or tiled roofs, polyurethane foam slab, polyester built up roofs Vapor barrier coating for walls and floor. Maintenance of existing roofs, masonry and concrete walls.

Application

Suitable for the waterproofing and protection of different kinds of spray applied polyurethane foam insulation, Waterproofing for roofs ranging from asphalt, asbestos cement, to concrete and terrazzo tiles, Recommended for both horizontal and inclined structure, Water proofing membrane for Flat Roofing Systems (Traditional and Inversed)



STAROOF 900

HIGH UV RESISTANT PRODUCT FOR EXTERNAL WATER PROOFING.



STAROOF 603

A SPECIAL ACRYLIC POLYMER RESINS AND ADDITIVES WITH EXCELLENT UV RESISTANCE.

Application

Star Proof HR900 is a single component, High solar reflectance keeps roofs cooler in high hot weather conditions as protective coating for thermal shocks. Tough and seamless membrane resists many harsh chemicals and bridges airline cracks. UV protection & display excellant dirt pick-up resistance and retain their flexibility long after aging.

Application

It is used for concrete roofs, polyester built up roofs, masonry, concrete walls, reflective and protective waterproof coating to concrete, asphalt and bitumen, asbestos cement, slates and tiles, zinc, timber surfaces, etc.


ACRYLIC ELASTOMERIC PU COATING



POLYURETHANE FOAM



POLYURETHANE



POLYUREA



Origin: Made in Greece

Products

- ➔ Ktisopour
- ➔ Ktisepox Hydro PR
- ➔ Ktisopour G Epoxy Grout
- ➔ All types of Epoxy Coating are Available



Car Park Solution



Transparent Solution



Origin: Made in Lebanon

Lightweight Screed

High concentration formulation
 30% saving of liquid cost against old formulators.
 Bubble consistency to get uniform mix
 Only 1 liter of SP 20 is enough to achieve
 1 CBM of L.W.C. for densities
 varying between 400 and 500 kg/m³
 Formulated for hot weathers



Origin: Made in UAE

WFP Crystal Slurry

WFP Crystal Slurry is a reactive, powdered, crystalline, rigid sealing slurry based on cement and special additives. WFP Crystal Slurry penetrates deep into the substrate and claws onto the substrate to achieve a very good bonding to the surface.



Origin: Made in UK




Products

- Single component (Cold applied)
- Double component (Cold applied)
- Hot Spray Applied
- ALIPHATIC Top Coats
- Multilayer Systems




EPOXY | PU | LIGHT WEIGHT CHEMICALS

**EFOAM**


Origin: Made in UAE
Thickness : 25mm to 100mm
Size : 1250mm x 600mm

Extruded Polystyrene Board**STAYROMAX**


Origin: Made in KSA
Thickness : 10mm to 100mm
Size : 2400mm x 1200mm

Expanded Polystyrene Board**FABCO**

Origin: Made in Saudi Arabia
Thickness : 30mm to 100mm
Density : 40 to 43kg/m³
Size : 2500mm x 600mm

PU YELLOW BOARD**ROCKWOOL**

Origin: Made in Saudi Arabia
Thickness : 25mm to 100mm
Density : 35-200kg/m³
Size : 1200mm x 600mm

ROCKWOOL INSULATION

Origin: Made in ITALY
Thickness : 0,5 mm to 4 mm
Size : 1mtr x 10 mtr

Aluminum Membrane Sheets**SOLARCOAT**

Origin: Made in TURKEY
Colour : White
Packaging: 20 Kg

Liquid Applied Membrane

Origin: Made in TURKEY
Thickness : 1,5mm to 4mm
Size : 1mtr x 10mtr
Self-Adhesive & Torch applied

**High U V resistant WHITE MEMBRANE****HEAT INSULATION SYSTEM****ITALPROFILI**

Origin: Made in ITALY
Size : 40mm to 120mm
Plastic & Steel Nails

Insulation Fastners**SOUDAL**


Origin: Made in BELGIUM
Colour : White
Packaging: 1Kg /5Kg /15 Kg

Polystyrene Adhesive




Origin: Made in Germany


WFP SEALING ELEMENT BK




WFP SEALING ELEMENT CORNER 90°




WFP EXPANSION JOINT CONNECTION




WFP SEALING ELEMENT CORNER FB




WFP EXPANSION JOINT CONNECTION



WFP SEALING ELEMENT BGL 80



WFP RUPTURE ELEMENT SFG



EXPANSION JOINT FILLER BOARDS



BACKUP RODS FOR EXPANSION AREA



EXPANSION JOINT FILLER & SEALANT



Waterstop Joints



Multibond



Acryrub

EXPANSION JOINT SYSTEM

Hammerl  Origin: Made in Germany




VAPOR BARRIER

Vapor barrier film with flame retardant according to building material Class-E for windproofing of full-frame rafters.



PE CONSTRUCTION FILM TRANSPARENT

Construction and cover foils made of PE-nature. Not UV stabilized.




TWO-LAYER DIMPLED MAT.

Made of polyethylene, high density, groundwater safe. Use in the foundation wall protection.



PIMPLE MAT WITH DRAINAGE FLEECE

Protects the foundation wall seal against damage and ensures safe drainage of the groundwater.




BITUMEN PROTECTION SHEET

Origin: Made in TURKEY
Thickness : 3mm, 4mm & 6mm
Size : 1000mm x 2000mm
Colour: Black



WFP PRE-TEC MEMBRANE PLUS

Origin: Made in GERMANY
Thickness : 1mm, 1.5mm & 2mm
Size : 1mtr x 20mtr
Colour: Yellow



PROTECTION SHEET

Origin: Made in LEBANON
Thickness : 2,2, 3, 4, 5, 6mm
Size : 1000mm x 2000mm
Colour: Blue

PROTECTION & SEPARATION LAYERS



Origin: Made in UAE







Exeed branded products have been at the forefront of the Geosynthetics industry. Continuous innovation has led to manufacture of superior products and made Exeed synonymous with highest standards of quality and performance .

With many years of experience in the Geosynthetics market , Exeed provides value engineered solutions for highways, coastal, railways, landfill, mines, tunnels, waterways, flood defence , landscapes and other sectors.

Exeed remains committed since the beginning to the development of innovative and cost effective Geosynthetics solutions. The company intended to lead the market in the design and manufacture of Geosynthetics and continue provide ground breaking solutions.

Exeed with manufacturing facility in UAE, is made available through a global distribution network. We have Distributors in all GCC.

Apart from supplying quality geotextile, EXEED can also supply High quality Bi-Axial and Uni-Axial Geogrids for pavement engineering, Gabion Boxes and soil reinforcement.

 <p>We offer thermal bonded & non thermal bonded geotextile products</p>	 <p>Exeed Geotextile range of products 90 to 1200 Grams per square meter</p>
 <p>We offer products up to 6 meter wide & length up to 200 meter per roll</p>	 <p>Highest grade shrink wrap packing of the geotextile roll ensures damage free product at our esteemed customer's doorsteps</p>
 <p>Geotextiles are available in raw white, black & grey color</p>	<p>PRIME GEOTEXTILE POLYPROPYLENE NEEDLE PUNCHED NON-WOVEN GEOTEXTILES</p>
 <p>Equipped to tailor make products to customers precise requirements</p>	<p>PRIME TECH POLYESTER NEEDLE PUNCHED NON-WOVEN GEOTEXTILES</p>





Origin: Made in Spain



EASY SPRAY HYDRAULIC HYDRAULIC PROPORTIONING UNIT

Easy Spray Hydraulic, of an advanced and compact design, is an easy-to-use, portable hydraulic unit. Its unique configuration the product tanks are placed on a chassis with wheels provides easy access to all types of working areas as well as a switch that allows an easy operation with no need of qualified personnel and a saving of time during the set up and application.



Origin: Made in USA



REACTOR A-25

The Reactor A-25 is a Graco-engineered spray foam proportioner that gives you the reliability you expect on the jobsite. It maintains consistent temperature control, even when you're spraying at maximum flow rates - resulting in better quality foam.



Origin: Made in India



PU HD-20/35 HYDRAULIC PROPORTIONING UNIT

Strong Performance in a reliable system. The HD-20/35 provides high output with smooth operation and low pulsation. Foam systems are optimized toward higher output with pressures up to 2000 psi. Some coatings can be sprayed through these systems.



HF-1600

A great system for insulation contractor. The lightweight, compact design of the Hydraulic HF-1600 allows for simple mobility around your plant or jobsite.



Origin: Made in Germany



EDAMA - ROOFMASTER



Origin: Made in Lebanon



AERCEL MACHINE



ROTOR



STATOR




Origin: Made in UAE

LIGHTWEIGHT FOAM (MODEL: DE-H)



- 01 Mixture tank capacity-1.35 cubic meter
- 02 Mixture gear RPM 47, mixture motor RPM 1450 HP 5.5
- 03 Chemical tank 2 nos. – capacity 150*2 liters
- 04 Stock tank capacity 50 liters
- 05 Air compressor motor RPM 2800 HP 5.5
- 06 Delivery pump motor RPM 1460 HP 20
- 07 Delivery pump with transmission shaft, stator (type-80 mm), rotor (type-80 mm)
- 08 Hugger motor RPM 1450 HP 4
- 09 Water tank Capacity 250 Liters
- 10 Electric panel board
- 11 Chassis with 4" rectangle tube, chasis length 4.5 meters & width 2 meters, complete machine weight 3.2 ton.

LIGHTWEIGHT FOAM (MODEL: DE-L)



- 01 Mixture tank capacity – 0.60 cubic meter
- 02 Mixture gear RPM 47, mixture motor RPM 1450 HP 5.5
- 03 Chemical tank 2 nos. – capacity 150*2 liters
- 04 Stock tank capacity 50 liters
- 05 Air compressor motor RPM 2800 HP 4
- 06 Delivery pump motor RPM 1460 HP 15
- 07 Delivery pump with transmission shaft, stator (type 65.5mm), rotor (type 65.5mm)
- 08 Hugger motor RPM 1450 HP4
- 09 Water tank Capacity 250 Liters
- 10 Electric panel board
- 11 Chassis with 4" rectangle tube, chasis length 3 meters & width 1.8 meters, complete machine weight 1.8 ton.

LIGHTWEIGHT FOAM MACHINE

A complete mobile unit for mixing, pumping and conveying foam concrete from ground level to the floor or terrace level. The mixing of the suitable materials inside this unit, allows an expansion of foam-concrete up to 5 times of its original volume and its specific weight is thus reduced. It is therefore ideal for thermal or acoustic insulation of floors. The equipment carries a twin diaphragm pump for pumping the water-foam additive solution, a wider reservoir containing water, the supply hopper feeding the piston pump with cement grout and the mixer-cylinder unit complete with gauges and control valves for production of foam concrete.

WFP Origin: Made in Germany
WATERPROOFING



INJECTION HOSE ECO

Length 50 m
(other lengths on demand)
Diameter 12 mm
Color Red



INJECT 1

Delivery form
1,1 kg (comp. A 1 kg + comp. B 0,1 kg)
Article number W060101
11 kg (comp. A 10 kg + comp. B 1 kg)




INJECTION PACKER

WFP Injection Packers are made of steel with a ball head nipple for injection with high pressure.



HAND PUMP

WFP Hand Pump is an injection device for application of WFP injection resins.



HOLDING GRID INJECTION HOSE

WFP Holding Grid Injection Hose is a metal mesh with a special mesh size, so that the penetration is not impaired.



PLASTIC CONNECTOR FOR INJECTION HOSE

WFP Plastic Connector For Injection Hose is a 68 mm screwable connector with a 3 mm open passage.



WFP GRIP HEAD

WFP Grip Head is a connector with four jaws to WFP Injection Packers.



INJECTION SPIDER DUO

It consist on a metal frame for fixing to the reinforcement steel. WFP Special Shutter Connector (red/white) can be easily mounted to the metal frame.

SEAL Experts® Origin: Made in India

Seal Experts offers products for repairing, leaking cracks in concrete bridge walls, decks, tanks, and foundations. Using epoxy and urethane methods are offered using high pressure injection pumps or dual manual injection guns. State of the art urethane grouts and epoxies are available. We specialize in the manufacturing of materials and equipment for all kinds of basement water issues including basement leaks, concrete crack injection, foundation repairs.



MANUAL INJECTION PUMP



SINGLE COMPONENT INJECTION GROUTING PUMP



DUAL COMPONENT INJECTION GROUTING PUMP



INJECTION PUMPS

INJECTION SYSTEM



WFP JOINT TAPE TPE 1

Length: 20 Mtr
 Thickness: 1 mm
 Roll width: 150 mm,200mm,250mm,
 300mm, 350mm, 400mm



WFP BETONITE WATER STOP TAPE

Length: 5 Mtr
 Width : 25 mm
 Height : 20 mm



WFP SWELLING RUBBER PROFILE


Length: 5 Mtr
 Dimensions: round Ø 15 mm
 round Ø 23 mm
 rectangle : 18 x 7 mm
 rectangle : 23 x 15 mm

DOUBLESTICK DOUBLE SIDED TAPE




DoubleStick is pure an advanced MicroSealant™ with a removable siliconized release liner on each side. Designed to bond two surfaces, even two surfaces made of two or more dissimilar materials. DoubleStick creates a tight, permanent, waterproof seal. DoubleStick remains flexible to temperatures as low as -56°C making it virtually impossible to thermally shock the seal causing a leak.

ROOFSEAL REPAIR AND SEALING TAPE



For use on virtually all roofs, RoofSeal/OneStep features a UV stable backing that is available in Black, Gray, Tan and White. With the exception of surface prep, RoofSeal/One-Step is a one-step permanent repair system for virtually all roof types, and roof accessories. RoofSeal/OneStep creates a waterproof, moisture, and air tight barrier with no additional sealing required. RoofSeal/OneStep remains flexible to temperatures as low as -56°C making it virtually impossible to thermally shock the seam causing a leak.

ALUMIBOND ALUMINIUM REPAIR AND SEALING TAPE



For use on virtually all roofs, walls, floors, gravity tanks, troughs, etc. UV stable and moisture tight, AlumiBond creates an air and vapor barrier. The thick 4 mil aluminum backing combined with an advanced MicroSealant™ creates a hard surface. AlumiBond bonds to a wide range of materials including carbon steel, aluminum, galvanized steel, aluminum foil, gypsum board, wood, rubber, tar, polyethylene, polypropylene, polystyrene, fiberglass, brick, concrete, masonry, rubber, thermoplastics, singleply roofing, etc.

SODAL SEALANT

TAPES & SEALANTS



- BITUMINOUS SEALANT
- ACRYLIC SEALANT
- POLYMERIC SEALANT
- POLYSULFIDE SEALANT
- POLYURETHANE SEALANT
- HYBRID POLYMER



 **ITALPROFILI** *Origin: Made in Italy*



**ANTI-BACKUP
ROOF DRAINS**



**CURVES,
CONNECTIONS, HOPPER**



**LEAF AND
GRAVEL GRATES**



**AIR VENTS/
VAPOUR EXTRACTORS**



DRAIN & SIPHON UNITS



**POLYETHYLENE,
BUTYL RUBBER, RESIN
& ELASTOMERIC BINDERS**



**HOT AIR WELDING
EQUIPMENT**



**AUTOMATIC HOT AIR
WELDING MACHINES**



SPREAD TANKER



**AIRLESS PAINT
SPRAYER**



**LASER
DISTANCE METER 50 M**



**TRAMEX RWS ROOF &
WALL INSPECTION KIT**

TOOLS & ACCESSORIES

CALLONI
ROOFING TORCHES AND EQUIPMENT

Origin: Made in Italy



ROOFING PROPANE
GAS TORCH – KIT



ROOFING GAS TORCH
ECOGAS



EQUIPMENTS FOR
WATERPROOFING



ACCESSORIES &
SPARE PARTS

ITALPROFILI
RESISTANT TO FIRE



RUBBER FLEXIBLE
HOSES



APZ GAS REGULATOR



TROWELS



ROLLERS



COVERALL



DEWALT SHOES



3M HARD HELMETS
HALF FACE MASK



3M QX EYEWEAR
OVER THE SPECTACLES



PAINT BRUSH



ROLLER BRUSH



MISCELLANEOUS



GRAY & GREEN MINERAL




DECORATIVE PEBBLE



BASE FOR ROOF SLAB



ROOF SLAB



CROSSGRIP (ROOF)



BITUMEN - ALUMINIUM REFLECTIVE PAINT



DECORATIVE PAINT FOR BITUMEN MEMBRANE



WATER BASED PRIMER

Latermix Cem Classic

Origin: Made in Italy



QUICK-DRYING LIGHTWEIGHT INSULATING PERMEABLE CONCRETE

IZOTEX[®] MAXI 250 WATERPROOFING MEMBRANE

Origin: Made in Italy



PRODUCT DESCRIPTION

IZOTEX MAXI 250 is flexible waterproofing membrane made of PP/PE/PP layers.

It is used for waterproofing and damp-proofing under ceramic tiles in bathrooms.

ADVANTAGES

100% Waterproof

IZOTEX MAXI 250 is 100% waterproof and high water pressure resistant.

Easy to Apply

IZOTEX MAXI 250 does not require any special equipment, products or even expertise to be applied. It can be cut using a sturdy craft knife or carpet scissors. It is applied by using C2 class tile adhesive.

Time-saving

IZOTEX MAXI 250 is applied just one layer, does not need several layers to be applied.

Flexible

IZOTEX MAXI 250 is a flexible material that allows ease of application at hard workable corners, floor and wall joints, tight angles.

Moisture Retardant

Thanks to its damp proof structure, it protects surfaces, where it is applied, from harmful effects caused by humidity and damp.

Ease of Bonding

Thanks to its fibrous texture, IZOTEX MAXI 250 has strong mechanical bonding to the adhesive and surface. Heat or other toxic elements are not used for bonding.

Light weighted

IZOTEX MAXI 250 is a lightweighted waterproofing membrane which allows easy to handle and apply.

Easy to transport and carry

IZOTEX MAXI 250 is packed in rolls that is easy to transport in construction site.

TECHNICAL CHARACTERISTICS

Apparent packed density (approx.)	500 kg/m ³
In-place density (approx.)	600 kg/m ³
Certified average compressive strength	2,5 N/mm ² (25 kg/cm ²)
Certified thermal conductivity λ	0,134 W/mK
Drying times (3% RH)	7 days (th. 5 cm)
Suggested thicknesses	≥ 5 cm
Bags required per 1 m ² of floor area	Q21 bags per 10mm depth
Package: bags each of 50litres on non-returnable wooden pallets, 60 bags/pallet - 3,0m ³ /pallet.	
Storage life: 12 months from date of packaging.	

OTHER PRODUCTS


Kavalani & Sons HIDD



(Head Office/Showroom)

P.O. Box 71, Bldg. No. 2513, Road 1535, Hidd 115
Bahrain Investment Wharf, Kingdom of Bahrain
Tel: +973 6999 0222, Fax: +973 6999 0220, E-Fax: +973 1791 0675

Kavalani & Sons SITRA



(Branch Office/Showroom)

Bldg. No. 775, Road 114
Sitra Industrial Area, Entrance 1, Sitra 601, Kingdom of Bahrain
Tel: +973 1773 2888, Fax: +973 1773 7379

 info@kavalani.com  www.kavalani.com

 /kavalaniwll

 /kavalani_bahrain

 /kavalani-and-sons

 #3800 0458